



TECHNICAL SPRAYS

## PRODUCT DATA 1633 - X1 STAINLESS STEEL CLEANER / POLISH

### DESCRIPTION

A foaming action, non-abrasive cleaner, degreaser and polish which will leave surfaces looking like new and protected with a dry to touch microscopic antistatic film. This will offer lasting protection against corrosion, staining, water and finger marks.

### MAIN PROPERTIES

Advanced cleaning and degreasing power - contains antistatic additives - non corrosive and non-abrasive - leaves microscopic and dry to touch protective film - 360 degree, any angle valve - A7 / C1 food industry accredited.

### RECOMMENDED USES

Formulated for use on matt, brushed and other stainless steel surfaces. Can also be used for cleaning aluminium, chrome, composites, laminates, enamel, ceramic and some plastic surfaces (test compatibility before use). Application areas: industrial equipment and control panels - food and beverage processing - Laboratory equipment - catering and kitchen equipment - escalators, elevators and stairwells - exhibition stands and displays - sign panels - washrooms and showers.

### TECHNICAL DATA

Appearance: Foam  
Colour: White

### SURFACE PREPARATION

Test for compatibility before use. Switch off or disconnect from electrical machinery before cleaning.

### DIRECTION FOR USE

Shake aerosol before use. Spray a light film on to surface from 20 to 30 cm. Do not over apply. Leave to soak for 1 minute, remove contaminations with a cloth or cleaning paper. Disconnect items from electricity before use.

### APPLICATION CONDITIONS

Apply at temperatures between 5° and 35°C.

### SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

### SHELLIFE / STORAGE CONDITIONS

3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Rust-Oleum Netherlands B.V.  
Braak 1, 4704 RJ  
P.O. Box 138, 4700 AC  
Roosendaal, The Netherlands  
T +31 (0)165 593 636  
F +31 (0)165 593 600  
info@rust-oleum.eu  
www.rust-oleum.eu  
www.x1techsprays.com

N.V. Martin Mathys S.A.  
Kolenbergstraat 23  
3545 Zelem  
Halen, Belgium  
T +32 (0)13 460 200  
F +32 (0)13 460 201  
info@rust-oleum.eu  
www.rust-oleum.eu  
www.x1techsprays.com

Rust-Oleum France S.A.S  
11, Rue Jules Verne, B.P. 6003  
95322 St-Leu-la-Forêt Cedex  
France  
T +33 (0)1 30 40 00 44  
F +33 (0)1 30 40 99 80  
info@rust-oleum.eu  
www.rust-oleum.eu  
www.x1techsprays.com

Rust-Oleum UK Ltd.  
PO Box 261  
Chester Le Street  
DH3 9EH  
United Kingdom  
T +44 (0)2476 717 329  
F +44 (0)2476 718 930  
info@rust-oleum.eu  
www.rust-oleum.eu  
www.x1techsprays.com



# SAFETY DATA SHEET

## X1 eXcellent Stainless Steel Cleaner

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Product name** : X1 eXcellent Stainless Steel Cleaner  
**Product description** : Aerosol. Cleaning solutions.  
**Product type** : Aerosol.

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Cleaning solutions.

#### 1.3 Details of the supplier of the safety data sheet

Rust-Oleum Netherlands BV, PO. Box 138, NL-4700 AC Roosendaal, The Netherlands  
Telephone: +31 (0) 165 593 636  
Fax no.: +31 (0) 165 593 600

Martin Mathys NV, Kolenbergstraat 23, B-3545 Zelem, Belgium  
Telephone no.: +32 (0) 13 460 200  
Fax no.: +32 (0) 13 460 201

**e-mail address of person responsible for this SDS** : rpmeurohas@ro-m.com

#### 1.4 Emergency telephone number

##### National advisory body/Poison Center

**Telephone number** : +44 (0) 207 858 1228

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

##### Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

**Classification** : F+; R12

**Physical/chemical hazards** : Extremely flammable.

See Section 16 for the full text of the R-phrases declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

**Hazard symbol or symbols** :



**Indication of danger** : Extremely flammable

**Risk phrases** : R12- Extremely flammable.

**SECTION 2: Hazards identification**

- Safety phrases** : S9- Keep container in a well-ventilated place.  
 S23- Do not breathe vapor or spray.  
 S51- Use only in well-ventilated areas.
- Supplemental label elements** : Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

**Special packaging requirements**

- Containers to be fitted with child-resistant fastenings** : Not applicable.
- Tactile warning of danger** : Not applicable.

**2.3 Other hazards**

- Other hazards which do not result in classification** : Not available.

**SECTION 3: Composition/information on ingredients**

**Substance/mixture** : Mixture

Product/ingredient name	Identifiers	%	Classification		Type
			67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	
hydrocarbons, C10-C12, iso-alkanes, < 2% aromatics	REACH #: 01-2119471991-29 EC: 923-037-2 CAS: 90622-57-4	10-20	R10  Xn; R65 R66 R53	Flam. Liq. 3, H226  Eye Irrit. 2, H319 Asp. Tox. 1, H304 Aquatic Chronic 4, H413	[1] [2]
butane	EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	5-10	F+; R12  <b>See Section 16 for the full text of the R-phrases declared above.</b>	Flam. Gas 1, H220 Press. Gas, H280  <b>See Section 16 for the full text of the H statements declared above.</b>	[2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard  
 [2] Substance with a workplace exposure limit  
 [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII  
 [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

Occupational exposure limits, if available, are listed in Section 8.

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.

**SECTION 4: First aid measures**

- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

**4.2 Most important symptoms and effects, both acute and delayed**

There are no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 3 and 15 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

**4.3 Indication of any immediate medical attention and special treatment needed**

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

See toxicological information (Section 11)

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

- Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.
- Unsuitable extinguishing media** : Do not use water jet.

**5.2 Special hazards arising from the substance or mixture**

- Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

**5.3 Advice for firefighters**

- Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
- Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.
- Additional information** : Container explosion may occur under fire conditions or when heated. Bursting aerosol containers may be propelled from a fire at high speed.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also Section 8 for additional information on hygiene measures.

- 6.2 Environmental precautions** : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

- 6.3 Methods and materials for containment and cleaning up** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Preferably clean with a detergent. Avoid using solvents. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

- 7.1 Precautions for safe handling** : Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8).

Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or watercourses.

### Information on fire and explosion protection

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapors in all cases. In such circumstances, they should wear a compressed-air-fed respirator during the spraying process and until the particulate and solvent vapor concentrations have fallen below the exposure limits.

- 7.2 Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations.
- Notes on joint storage**  
Keep away from: oxidizing agents, strong alkalis, strong acids.
- Additional information on storage conditions**  
Observe label precautions. Do not store above the following temperature: 35°C (95°F). Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept

**SECTION 7: Handling and storage**

upright to prevent leakage.

**7.3 Specific end use(s)****Recommendations** : Not available.**Industrial sector specific solutions** : Not available.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters**Occupational exposure limits

Product/ingredient name	Exposure limit values
hydrocarbons, C10-C12, iso-alkanes, < 2% aromatics	<b>EH40/2005 WELs (United Kingdom (UK), 10/2007).</b> STEL: 850 mg/m <sup>3</sup> , (as turpentine (150 ppm)) 15 minute(s). Form: Vapor TWA: 566 mg/m <sup>3</sup> , (as turpentine (100 ppm)) 8 hour(s). Form: Vapor
butane	<b>EH40/2005 WELs (United Kingdom (UK), 8/2007).</b> STEL: 1810 mg/m <sup>3</sup> 15 minute(s). STEL: 750 ppm 15 minute(s). TWA: 1450 mg/m <sup>3</sup> 8 hour(s). TWA: 600 ppm 8 hour(s).

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

Derived effect levels

No DELs available.

Predicted effect concentrations

No PECs available.

**8.2 Exposure controls**

**Appropriate engineering controls** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.

Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety glasses with side shields. (EN166)

Skin protection

**Hand protection** : Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**SECTION 8: Exposure controls/personal protection**

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Wear overalls or long sleeved shirt. (EN 1149-1)
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.  
Recommended: organic vapor (Type A) and particulate filter (EN 140) .
- Environmental exposure controls** : Do not allow to enter drains or watercourses.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****Appearance**

- Physical state** : Liquid. [Aerosol.]
- Color** : Off-white.
- Odor** : Pleasant. [Slight]
- Odor threshold** : Not available.
- pH** : 7 to 8
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** : Not available.
- Flash point** : Closed cup: -75°C
- Evaporation rate** : >1 (butyl acetate = 1)
- Flammability (solid, gas)** : Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.  
Slightly flammable in the presence of the following materials or conditions: shocks and mechanical impacts.  
Container explosion may occur under fire conditions or when heated. Vapor may travel considerable distance to source of ignition and flash back.
- Burning time** : Not applicable.
- Burning rate** : Not applicable.
- Upper/lower flammability or explosive limits** : Lower: 3%  
Upper: 18%
- Vapor pressure** : >400 kPa [20°C]
- Vapor density** : >1 [Air = 1]
- Relative density** : 0.83
- Solubility(ies)** : Not available.
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : 405°C
- Decomposition temperature** : Not available.
- Viscosity** : Not available.
- Explosive properties** : Highly explosive in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and shocks and mechanical impacts.
- Oxidizing properties** : Not available.

**9.2 Other information**

- Type of aerosol** : Foam
- No additional information.

**SECTION 10: Stability and reactivity**

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : Stable under recommended storage and handling conditions (see section 7).
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.
- 10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced. If involved in a fire, toxic gases including CO, CO<sub>2</sub> and smoke can be generated.

**SECTION 11: Toxicological information****11.1 Information on toxicological effects**

There are no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 3 and 15 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

**Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
hydrocarbons, C10-C12, iso-alkanes, < 2% aromatics	LD50 Dermal	Rabbit	>2000 mg/kg	-
isobutane	LD50 Oral	Rat	>5000 mg/kg	-
	LC50 Inhalation Vapor	Rat	658000 mg/m <sup>3</sup>	4 hours
butane	LCLo Inhalation Gas.	Rat	1041000 mg/m <sup>3</sup>	2 hours
	LC50 Inhalation Gas.	Rat	658000 mg/m <sup>3</sup>	4 hours

**Conclusion/Summary** : Not available.

**Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
hydrocarbons, C10-C12, iso-alkanes, < 2% aromatics	Skin - Mild irritant	Rabbit	-	-	-
	Eyes - Mild irritant	Rabbit	-	-	-

**Conclusion/Summary** : Not available.

**Sensitization**

Product/ingredient name	Route of exposure	Species	Result
hydrocarbons, C10-C12, iso-alkanes, < 2% aromatics	skin	Rabbit	Not sensitizing

**Conclusion/Summary** : Not available.



**SECTION 11: Toxicological information****Mutagenicity**

**Conclusion/Summary** : Not available.

**Carcinogenicity**

**Conclusion/Summary** : Not available.

**Reproductive toxicity**

**Conclusion/Summary** : Not available.

**Teratogenicity**

**Conclusion/Summary** : Not available.

**Other information** : Not available.

**SECTION 12: Ecological information****12.1 Toxicity**

There are no data available on the preparation itself.  
Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment but contains a substance or substances dangerous for the environment. See section 3 for details.

Product/ingredient name	Result	Species	Exposure
hydrocarbons, C10-C12, iso-alkanes, < 2% aromatics	Acute EC50 >100 mg/l	Fish - Chaetogammarus marinus	24 hours
	Acute LC50 >1000 mg/l	Fish	96 hours
	Acute NOEC 1000 mg/l	Algae - pseudokirchneriella subcapitata	72 hours
	Chronic NOEC 0.025 mg/l	Daphnia	21 days

**Conclusion/Summary** : Not available.

**12.2 Persistence and degradability**

Product/ingredient name	Test	Result	Dose	Inoculum
hydrocarbons, C10-C12, iso-alkanes, < 2% aromatics	-	31.3 % - Inherent - 28 days	-	-

**Conclusion/Summary** : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
hydrocarbons, C10-C12, iso-alkanes, < 2% aromatics	-	-	Inherent

**12.3 Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
hydrocarbons, C10-C12, iso-alkanes, < 2% aromatics	>3	-	high
isobutane	2.8	-	low
butane	2.89	-	low
propane	2.36	-	low

**12.4 Mobility in soil**

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

**12.5 Results of PBT and vPvB assessment**

**PBT** : Not applicable.

**SECTION 12: Ecological information**

**vPvB** : Not applicable.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

**SECTION 13: Disposal considerations**

Do not allow to enter drains or watercourses.  
 Dispose of according to all federal, state and local applicable regulations.

**13.1 Waste treatment methods**

**Product**

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

**Hazardous waste** : Yes.  
**European waste catalogue (EWC)** : The European Waste Catalogue classification of this product, when disposed of as waste, is:  
 11 01 13\* degreasing wastes containing dangerous substances.  
 If this product is mixed with other wastes, this code may no longer apply. If mixed with other wastes, the appropriate code should be assigned. For further information, contact your local waste authority.


**Packaging**

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Spraycans	15 01 04 metallic packaging

**Special precautions** : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

**SECTION 14: Transport information**

	ADR/RID	IMDG	IATA
<b>14.1 UN number</b>	1950 LQ	1950 LQ	1950
<b>14.2 UN proper shipping name</b>	AEROSOLS, Flammable [Limited quantity]	AEROSOLS, Flammable [Limited quantity]	AEROSOLS, Flammable
<b>14.3 Transport hazard class(es)</b>	2	2.1	2.1 
<b>14.4 Packing group</b>	-	-	-
<b>14.5 Environmental hazards</b>	No.	No.	No.

**SECTION 14: Transport information**

<b>14.6 Special precautions for user</b>	<b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	<b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	<b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
<b>Additional information</b>	<b>Limited quantity:</b> LQ2  <b>Remarks:</b> (≤ 5L: ) Limited Quantity - ADR/IMDG 3.4  ADR Tunnel Code: (D)	<b>Emergency schedules (EmS):</b> F-D + S-U  <b>Remarks:</b> Limited Quantity - ADR/IMDG 3.4	<b>Passenger and Cargo Aircraft</b> Quantity limitation: 75 kg Packaging instructions: 203 <b>Cargo Aircraft Only</b> Quantity limitation: 150 kg Packaging instructions: 203 <b>Limited Quantities - Passenger Aircraft</b> Quantity limitation: 30 kg Packaging instructions: Y 203

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** : Not available.

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

**CN code** : 3402 90 90

**EU Regulation (EC) No. 1907/2006 (REACH)****Annex XIV - List of substances subject to authorization****Substances of very high concern**

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

**Other EU regulations**

**VOC for Ready-for-Use Mixture** : Not applicable.

**Europe inventory** : Not determined.

**Black List Chemicals** : Not listed

**Priority List Chemicals** : Not listed

**SECTION 15: Regulatory information**

Aerosol dispensers :

3

31.2% by mass of the contents are flammable.

Product/ingredient name	List name	Name on list	Classification	Notes
butane	UK Occupational Exposure Limits EH40 - WEL	butane	Carc.	-

**15.2 Chemical Safety Assessment** : This product contains substances for which Chemical Safety Assessments are still required.

**SECTION 16: Other information**

✔ Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
 DNEL = Derived No Effect Level  
 EUH statement = CLP-specific Hazard statement  
 PNEC = Predicted No Effect Concentration  
 RRN = REACH Registration Number

**Full text of abbreviated H statements** : H220 Extremely flammable gas.  
 H226 Flammable liquid and vapor.  
 H280 Contains gas under pressure; may explode if heated.  
 H304 May be fatal if swallowed and enters airways.  
 H319 Causes serious eye irritation.  
 H413 May cause long lasting harmful effects to aquatic life.

**Full text of classifications [CLP/GHS]** : Aquatic Chronic 4, H413 AQUATIC TOXICITY (CHRONIC) - Category 4  
 Asp. Tox. 1, H304 ASPIRATION HAZARD - Category 1  
 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
 Flam. Gas 1, H220 FLAMMABLE GASES - Category 1  
 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3  
 Press. Gas Comp. Gas, H280 GASES UNDER PRESSURE - Compressed gas

**Full text of abbreviated R phrases** : R12- Extremely flammable.  
 R10- Flammable.  
 R65- Harmful: may cause lung damage if swallowed.  
 R66- Repeated exposure may cause skin dryness or cracking.  
 R53- May cause long-term adverse effects in the aquatic environment.

**Full text of classifications [DSD/DPD]** : F+ - Extremely flammable  
 Xn - Harmful



**Version** : 1  
**Date of printing** : 23-10-2012.  
**Date of issue/ Date of revision** : 23-10-2012.  
**Date of previous issue** : No previous validation.

Notice to reader

## SECTION 16: Other information

*The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.*

© Rust-Oleum Netherlands B.V. / Martin Mathys N.V.



*This is to certify that*

# Stainless Steel Cleaner aerosol

supplied by

**RUST-OLEUM Netherlands B.V.**

Braak 1, 4704 RJ, P.O. Box 138, 4700 AC, Roosendaal, The Netherlands

has been registered by InS Services



## Metal Cleaners for Surfaces with No Food Contact General Nonprocessing Area Product

This product is acceptable as a metal cleaner or polish on surfaces where there is no food contact, provided that all odours associated with the product have dissipated before food or packaging are re-exposed to the area. All food products and packaging should be removed from the area or covered prior to use.

This product is also acceptable for use in areas where there is no food processing or open storage, provided that there is no possibility of any odour or fragrance entering a food processing or open storage area. Treated items used in food processing areas must be suitably cleaned and rinsed with potable water before being returned.

Signed: .....

*S. J. Skone*  
InS Services

Date: 14 September 2012

InS Services (UK) Ltd.

[www.insservices.eu](http://www.insservices.eu)